

## Loader Ticket Phoenix

Loader Ticket Phoenix - Loaders have been built to be able to work just about anywhere. They offer optimal maneuverability and traction due to a heavy-duty oscillating joint that offers 45-degree rotating angles toward the left and right, with 10 degrees of oscillation in both directions. Access is granted to confined and tight spaces by narrow engine widths. Majority of skid-steer loaders with comparable operating capacities are unable to compete. The tires and bucket on the Gehl machine follow a constant turn radius also. This means the back tires of the loader follow the path of the front tires.

Fantastic hydraulic performance, with numerous time-saving features on the Gehl articulated loaders, provides customers with the hydraulic power and precision they have come to expect from all Gehl equipment. Bucket float and lift arm features permit these machines to be able to carry out rearward level and light scraping actions. Flat-face couplers, along with the two easily reachable auxiliary hydraulic lines power numerous tools and make changing the attachments an easy job to complete.

Gehl articulated loaders have distinctively built hoist arms which are made so as to attain maximum strength, fast cycle times and great visibility. The specialized linkage pattern allows for mechanized self-leveling action in both the up and down directions. It can also simply execute exceptional bucket dump angles at the top and mid ranges of the lift path together with offering excellent forward reach. Models 140 and 340 have parallel type linkage and the model 540 has "Z" bar type linkage. These linkage layouts offer fantastic bucket breakout forces from two thousand four hundred thirty three pounds on the model 140 to ten thousand seven hundred forty nine pounds on the model 540.

Gehl articulated loaders are popular all over the world for their unsurpassed visibility, ease of operation and supreme ergonomics. The 340 and 540 machines have a total cab enclosure preference obtainable. This offers better safety and comfort for the individual operating it. Safe operation and 360 degree visibility is maintained by placing the one operating it above the load to ensure an exceptional view of the accessory. An inching pedal allows the individual operating it to vary ground speed whilst maintaining a fixed engine velocity. This feature allows the individual operating it to optimally run accessories while making certain precise engine speed control. A multi-function joystick controls the float, differential lock and auxiliary hydraulic functions, bucket, travel direction and the lift arm.